

To use this interactive guide

1. Download PDF file
2. Open with Adobe Acrobat, Chrome or Microsoft Edge
3. Click on the luminaire image to see available NX Lighting Controls Options

Area					
Kim Lighting	Beacon	EXO			
Ouro Edge Lit (UR20)	Ouro Strike (UR20, UR28)	Altitude®	Viper Area	Ratio	SLING Area (ASL1, ASL2)

Wall				
Kim Lighting	Beacon	EXO	Beacon	Kim Lighting

Wall Director® (WDS)	Wall Director® (WDM)	Ratio (RWL)	LitePak (LNC2)	Geopak (TRP2L)	Geopak (RDI2L)	Geopak (QSP2L)	Prevent (PVNTR)	Prevent (PVNT)
----------------------	----------------------	-------------	----------------	----------------	----------------	----------------	-----------------	----------------

Bollard	Garage				Flood		
Kim Lighting	Kim Lighting	Beacon			Kim Lighting	Beacon	
Pavilion (PA7S, PA7R)	PGL8®	Drive (SRT1)	Drive (SRT2)	Lumasquare® (LSQ)	KFL3	Viper Flood (VP-F)	Ratio (RFL)

Control Option Ordering Logic & Description	Control Option Functionality									Control Option Components
	Networkable	Grouping	Scheduling	Occupancy	Daylight Harvesting	0-10V Dimming	On/Off Control	Bluetooth App Programming	Sensor Height	
NX Wireless										
Independent										

Default Settings

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Current is under license. Other trademarks and trade names are those of their respective owners.